



KX-MB2130 FAX PANASONIC

		KX-MB2137	KX-MB2130
General			
Printing Process		Laser	
Recording Paper Size (Simplex)		-Input Tray: A4, LTR, LGL, B5(JIS/ISO), Folio (216 x 330 mm), Oficio (216 x 340 mm), 16K -Manual tray: A5, A4, LTR, LGL, B5(JIS/ISO), Folio (216 x 330 mm), Oficio (216 x 340 mm), 16K, Envelope #10/DL/YOUKEI #4/CHOUKEI #3/CHOUKEI #4, Custom (W: 210-216 mm, L: 279-356 mm)	
Recording Paper Capacity*1		Max: 251 sheets [Standard input tray: 250 sheets / Manual tray: 1 sheet]	
Paper Output Capacity		100 sheets	
ADF	Capacity	35 sheets	
	Document size	A4, A5, LTR, LGL, B5(JIS), B5(ISO), Folio (216 x 330 mm), Oficio (216 x 340 mm), 16K	
LCD Display		16 digits / 2 lines with back-light	
Memory Size		128 MB	64 MB
Monthly duty	Average	1,200 pages	1,200 pages
	Maximum	30,000 pages	12,000 pages
Power Consumption		Maximum: Approx. 1000 W Copy: Approx. 500 W, Ready: Approx. 65 W Sleep: Less than 3.3 W*2	
Noise level	Standby	Less than 25 dBA*3	
	Copying	Less than 52 dBA*3	
Computer Interface		100Base-TX/10Base-T, USB2.0	
Dimensions (W x D x H)		410 x 400 x 320 mm (Including handset: 447 x 400 x 320 mm)	
Weight		Approx. 12 kg	

Printer		
Print Speed	Up to 26 ppm (A4)	
Duplex Printing	Yes (A4, LTR, LGL, 216 x 330 mm, 216 x 340 mm)	
Duplex Productivity (A4)	92 % (24 ppm)	
Print Resolution	Up to 2400 x 600 dpi	Up to 600 x 600 dpi
First Print Time	8.5 s (from standby)	
Emulation	GDI	
Supported OS	Windows® XP, Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Windows Server® 2008, Windows Server® 2012, Mac OS X 10.5 - 10.10* ⁴ , Linux®* ⁵	
Copier		
Copy Speed ^{*6}	Up to 26 cpm (A4)	
Copy Resolution	Up to 600 x 600 dpi	
Multi-Copy	99 pages	
First Copy Time	Approx. 10.5 s (ADF)	
Reduction / Enlargement	25 % - 400 % (1 % step)	
Copy Function	Quick ID, N-in-1, Separate N-in-1, Poster, Image Repeat, Booklet, Edge/Margin	
Scanner		
Color / Mono Scan	Yes / Yes	
Scan Resolution	Optical: Up to 600 x 1200 dpi (Flatbed) / Interpolated: Up to 19200 x 19200 dpi	
Scan Function	Scan to PC / Email Address / FTP / SMB	
Supported OS	Windows® XP, Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Mac OS X 10.5 - 10.10* ⁴ , Linux®* ⁵	
Fax		
Modem Speed	33.6 kbps - 2.4 kbps with automatic fallback	
Memory Size	Total 3 MB (Reception: Approx. 80 pages* ⁷ , Transmission: Approx. 150 pages* ⁷)	
Address book	100	
Fax / Tel Switch	Yes	
Fax to Email	Yes	
Web Fax Preview	Yes	

*1 Depending on the type of paper.

*2 When only USB interface is connected and LAN is OFF mode. Power consumption in sleep mode depends on machine condition.

*3 Sound Pressure Level based on ISO7779 bystander position. It depends on the measuring method.

*4 Mac OS X 10.10 driver is provided via web download.

*5 Supported Linux distribution: Red Hat® Enterprise Linux® Desktop 5/6/7, Ubuntu® 10/11/12/13/14. Driver is provided via web download.

*6 Continuous copy of a single original.

*7 Based on the ITU-T No. 1 Test Chart in standard resolution.

- Windows, Windows Vista, Windows Server are registered trademarks of Microsoft Corporation in the United States and/or other countries.
- Mac and OS X are trademarks of Apple Inc., registered in the U.S. and other countries.
- Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.
- Red Hat and Red Hat Enterprise Linux are registered trademarks or trademarks of Red Hat, Inc. in the United States and/or other countries.
- Ubuntu is a registered trademark or a trademark of Canonical Ltd. in the U.S. and other countries.